



PV4

PV4 4,8mm pixel pitch, Ultra high 4mm Outdoor SMD LED display solution



The DLG PV4 is a modular rugged Outdoor LED tile that provides powerful imagery in combination with 24/7 reliability and a low cost of ownership. With less power consumption and a lighter weight than similar products, the PV4 is a perfect fit for digital signage and sports , hotel , home applications.

Excellent brightness, color and contrast

The PV4 tiles deliver an excellent balance between brightness, color and contrast. By nature, their low maintenance requirements and proven track record result in an exceptionally low total cost of ownership.



Technical specifications

PV4

Pixel pitch	4,8 mm
Brightness	7000 nits
LED type	Cree® PLCC4 3-in-1 SMD LED CLPPB-FKB
Pixel density	43.401 dots/sqm
Viewing angle	Hor. viewing angle / Vert. viewing angle 145° + (min. 50% brightness)
Operational humidity	operating: 0- 85% storage: 0 90%
Lifetime	100,000 hrs (@50 % brightness)
Power consumption	180 W/sqm 70 W/sqm typical
Operation power voltage	200 240 V / 50 60 Hz
Tile size (WxHxD) in mm	1000mm x 500mm x 80mm
Weight	8,5 kg (per cabinet)
IP rating	IP65/IP54
Processing	16 bit/color
Refresh rate	≥3840 Hz
Operating temperature	-30 to +50°C (-4° to 122°F)
Serviceability	Front operated
Max. stacking	20 tiles
Max. hanging	40 tiles
Operatable digitizer	DV2000/X1
Interfaces/Ports	CAT5-6
Certifications	ETL, CE, FCC Class A, RoHS



Video Controller Systems



VX6s

All-in-One Controller

The VX6s is an all-in-one controller that integrates sending card functions with video processing. Designed with powerful video processing capability, it supports 7 video inputs and 6 Gigabit Ethernet outputs.

Based on the powerful FPGA processing platform, the VX6s supports multiple transition effects, such as quick seamless switching and fade, providing flexible display controlling and outstanding video presentations.

The VX6s is equipped with an expansion card which can connect a USB drive to play the media files stored in it. By connecting a mouse and monitor, the USB playback can be intuitively monitored in real-time.