




## PV18/25

PV18/25mm pixel pitch, Ultra high 18/25mm outdoor DIP LED display solution



The DLG PV18/25 is a modular rugged outdoor LED tile that provides powerful imagery in combination with 24/7 reliability and a low cost of ownership. With less power consumption and a lighter weight than similar products, the PV18/25 is a perfect fit for digital signage and sports , hotel , LED MEDIA FACADE

### Excellent brightness, color and contrast

The PV18/25 tiles deliver an excellent balance between brightness, color and contrast. By nature, their low maintenance requirements and proven track record result in an exceptionally low total cost of ownership.



## Technical specifications

## PV18/25mm

Pixel pitch	18/25 mm
Brightness	7500 nits
LED type	Nichia® LED
Pixel density	1600-4000 dots/sqm
Viewing angle	Hor. viewing angle / Vert. viewing angle 145° + (min. 50% brightness)
Operational humidity	operating: 0- 85% storage: 0 90%
Lifetime	100,000 hrs (@50 % brightness)
Power consumption	600 W/sqm 150 W/sqm typical
Operation power voltage	200 240 V / 50 60 Hz
Tile size (WxHxD) in mm	1400mm x 400mm
Weight	18 kg ( per sqm)
IP rating	IP66
Processing	16 bit/color
Refresh rate	1,600 Hz
Operating temperature	-30 to +50°C (-4° to 122°F)
Serviceability	Back / Front operated
Max. stacking	No limit
Max. hanging	No limit
Operatable digitizer	DV2000/X1
Interfaces/Ports	CAT6
Certifications	ETL, CE, FCC Class A, RoHS